


## Light Shooter Adjustable No Trim

■ 03.6524.14A - Black

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




## Main specifications

Number of heads	1	Net lumen (lm)	474
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	25
Beam angle C90-270 (°)	25



Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1931	0.44
2	483	0.88
3	215	1.32
4	121	1.75
5	77	2.19

Luminous flux luminaire  
474 lm (EXTREME CUT OFF)

## Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	12.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

## Physical

Color	Black	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	170		
Weight (kg)	0.45		
Tilt (°)	40		

## Note

Accessory to reach IP54 incorporated. Pre-installation frame included in No Trim versions.



## Light Shooter Adjustable No Trim



---

Honeycomb  
08.8412.14



---

Elliptical light distribution lens  
08.8041.68