


Light Shooter Adjustable No Trim Dimmable

■ 03.6521.14ADA - Black

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	491
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	25



Beam Angle: 25°

h(m)	E(lx)	D(m)
1	2000	0.44
2	500	0.88
3	222	1.32
4	125	1.75
5	80	2.19

Luminous flux luminaire
491 lm (EXTREME CUT OFF)

Electrical


Dimmable	Yes
Driver	Remote included
Driver type	Dimmable 1-10V, Dimmable DALI 1
Emergency	Without
Insulation class	II

Physical

Color	Black	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	170		
Weight (kg)	0.45		
Tilt (°)	40		

Note

LED: All the models include an accessory for IP54. Pre-installation frame included in No Trim versions.



Light Shooter Adjustable No Trim Dimmable



Elliptical light distribution lens
08.8041.68



Honeycomb
08.8412.14