


## Light Shooter Adjustable No Trim Dimmable

03.6521.40ADA - White

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	491
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	10W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	25



<b>Beam Angle:</b>	25°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	2000	0.44	
2	500	0.88	
3	222	1.32	
4	125	1.75	
5	80	2.19	

Luminous flux luminaire  
491 lm (EXTREME CUT OFF)

### Electrical


<b>Dimmable</b>	Yes
<b>Driver</b>	Remote included
<b>Driver type</b>	Dimmable 1-10V, Dimmable DALI 1
<b>Emergency</b>	Without
<b>Insulation class</b>	II

### Physical

<b>Color</b>	White	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable		
<b>Recessed depth (mm)</b>	170		
<b>Weight (kg)</b>	0.45		
<b>Tilt (°)</b>	40		

### Note

Accessory to reach IP54 incorporated. Pre-installation frame included in No Trim versions.



## Light Shooter Adjustable No Trim Dimmable



---

Honeycomb  
08.8412.14



---

Elliptical light distribution lens  
08.8041.68