


Light Shooter Adjustable Trim

03.6501.40A - White

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	491
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	25
Beam angle C90-270 (°)	25



Beam Angle: 25°

h(m)	E(lx)	D(m)
1	2000	0.44
2	500	0.88
3	222	1.32
4	125	1.75
5	80	2.19

Luminous flux luminaire
491 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	12.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical

Color	White	Tilt (°)	40
Orientation	Adjustable	Rotation (°)	360
Trim	yes		
Recessed depth (mm)	170		
Weight (kg)	0.45		

Note

Accessory to reach IP54 incorporated.



Light Shooter Adjustable Trim



Honeycomb
08.8412.14



Elliptical light distribution lens
08.8041.68