



03.6503.40A - White

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.



Number of heads	1	Net lumen (lm)	317
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Beam Angle: 13°

h(m)	E(lx)	D(m)
1	3885	0.22
2	971	0.44
3	432	0.66
4	243	0.88
5	155	1.10

Luminous flux lumineuse
317 lm (EXTREME CUT OFF)

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	12.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Color	White	Tilt (°)	40
Orientation	Adjustable	Rotation (°)	360
Trim	yes		
Recessed depth (mm)	170		
Weight (kg)	0.45		

Accessory to reach IP54 incorporated.

Light Shooter Adjustable Trim



Honeycomb
08.8412.14



Elliptical light distribution lens
08.8041.68