


## Light Shooter Adjustable Trim

03.6504.40A - White

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 474                 |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 10W   | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 25        |
| Beam angle C90-270 (°) | 25        |



Beam Angle: 25°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1931  | 0.44 |
| 2    | 483   | 0.88 |
| 3    | 215   | 1.32 |
| 4    | 121   | 1.75 |
| 5    | 77    | 2.19 |

Luminous flux luminaire  
474 lm (EXTREME CUT OFF)

## Electrical

|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 12.00           | Insulation class | II      |
| Dimmable       | No              |                  |         |
| Driver         | Remote included |                  |         |
| Driver type    | Non Dimmable    |                  |         |

## Physical

|                     |            |              |     |
|---------------------|------------|--------------|-----|
| Color               | White      | Tilt (°)     | 40  |
| Orientation         | Adjustable | Rotation (°) | 360 |
| Trim                | yes        |              |     |
| Recessed depth (mm) | 170        |              |     |
| Weight (kg)         | 0.45       |              |     |

## Note

Accessory to reach IP54 incorporated.



## Light Shooter Adjustable Trim



---

Honeycomb  
08.8412.14



---

Elliptical light distribution lens  
08.8041.68