


Light Shooter Adjustable Trim Dimmable

■ 03.6500.14ADA - Black

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 328 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 10W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|---------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 13° |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 13° | | |
| | h(m) | E(lx) | D(m) |
| | 1 | 4026 | 0.22 |
| | 2 | 1006 | 0.44 |
| | 3 | 447 | 0.66 |
| | 4 | 252 | 0.88 |
| | 5 | 161 | 1.10 |

Luminous flux luminaire
328 lm (EXTREME CUT OFF)

Electrical


| | |
|-------------------------|---------------------------------|
| Dimmable | Yes |
| Driver | Remote included |
| Driver type | Dimmable 1-10V, Dimmable DALI 1 |
| Emergency | Without |
| Insulation class | II |

Physical

| | | | |
|----------------------------|------------|---------------------|-----|
| Color | Black | Rotation (°) | 360 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 170 | | |
| Weight (kg) | 0.45 | | |
| Tilt (°) | 40 | | |

Note

LED: All the models include an accessory for IP54.



Light Shooter Adjustable Trim Dimmable



Honeycomb
08.8412.14



Elliptical light distribution lens
08.8041.68