



03.6529.40A - White

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.



Number of heads	1	Net lumen (lm)	332
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	12
Beam angle C90-270 (°)	12




Luminous flux lumineuse  
332 lm (EXTREME CUT OFF)

Beam Angle:	12°		
	<u>h(m)</u>	<u>E(lx)</u>	<u>D(m)</u>
1	3801	0.22	
2	950	0.43	
3	422	0.65	
4	238	0.86	
5	152	1.08	

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	12.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Color	White
Orientation	Fixed
Recessed depth (mm)	160
Weight (kg)	0.45

Accessory to reach IP54 incorporated. Pre-installation frame included in No Trim versions.



## Light Shooter Fixed No Trim



---

Honeycomb  
08.8412.14



---

Elliptical light distribution lens  
08.8041.68