


Light Shooter Fixed No Trim

■ 03.6530.14A - Black

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	544
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	25
Beam angle C90-270 (°)	25



Beam Angle: 25°		
h(m)	E(lx)	D(m)
1	2098	0.44
2	524	0.88
3	233	1.33
4	131	1.77
5	84	2.21


Luminous flux luminaire
544 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	12.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical

Color	Black
Orientation	Fixed
Recessed depth (mm)	160
Weight (kg)	0.45



Note

LED: All the models include an accessory for IP54. Pre-installation frame included in No Trim versions.

Light Shooter Fixed No Trim



Elliptical light distribution lens
08.8041.68



Honeycomb
08.8412.14