



Light Shooter Fixed No Trim Dimmable

■ 03.6527.14ADA - Black

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 564 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 10W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|---------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 25 |



Beam Angle: 25°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 2173 | 0.44 |
| 2 | 543 | 0.88 |
| 3 | 241 | 1.33 |
| 4 | 136 | 1.77 |
| 5 | 87 | 2.21 |

Luminous flux luminaire
564 lm (EXTREME CUT OFF)

Electrical

| | |
|-------------------------|---------------------------------|
| Dimmable | Yes |
| Driver | Remote included |
| Driver type | Dimmable 1-10V, Dimmable DALI 1 |
| Emergency | Without |
| Insulation class | II |

Physical

| | |
|----------------------------|-------|
| Color | Black |
| Orientation | Fixed |
| Recessed depth (mm) | 160 |
| Weight (kg) | 0.45 |

Note

LED: All the models include an accessory for IP54. Pre-installation frame included in No Trim versions.

Light Shooter Fixed No Trim Dimmable



Elliptical light distribution lens
08.8041.68



Honeycomb
08.8412.14