


## Light Shooter Fixed No Trim Dimmable

03.6527.40ADA - White

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 564                 |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 10W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                    |           |
|--------------------|-----------|
| Lighting type      | Direct    |
| LED type           | Power LED |
| Light distribution | Symmetric |
| Optical type       | Flood     |
| Beam angle (°)     | 25        |



Beam Angle: 25°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2173  | 0.44 |
| 2    | 543   | 0.88 |
| 3    | 241   | 1.33 |
| 4    | 136   | 1.77 |
| 5    | 87    | 2.21 |

Luminous flux luminaire  
564 lm (EXTREME CUT OFF)

## Electrical

|                  |                                 |
|------------------|---------------------------------|
| Dimmable         | Yes                             |
| Driver           | Remote included                 |
| Driver type      | Dimmable 1-10V, Dimmable DALI 1 |
| Emergency        | Without                         |
| Insulation class | II                              |

## Physical

|                     |       |
|---------------------|-------|
| Color               | White |
| Orientation         | Fixed |
| Recessed depth (mm) | 160   |
| Weight (kg)         | 0.45  |

## Note

Accessory to reach IP54 incorporated. Pre-installation frame included in No Trim versions.



## Light Shooter Fixed No Trim Dimmable



---

Honeycomb  
08.8412.14



---

Elliptical light distribution lens  
08.8041.68