



Light Shooter HP Adjustable No Trim

■ 03.6571.14A - Black

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.

Main specifications

 Number of heads
 1

 Lamp category
 LED

 Power (W)
 11 W

 CCT (K)
 3000 K

 CRI
 90

Net lumen (lm) 5'
Mountings C


Mountings Ceiling re Environment Indoor dry

598

Ceiling recessed Indoor dry location

Optical

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Flood
Beam angle (°) 28
Beam angle C90-270 (°) 28



E(lx) h(m) D(m) 2015 0.50 2 504 1.01 3 1.51 224 4 126 2.02 5 81 2.52

Beam Angle:

28°

Luminous flux luminaire 598 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz) 50/60 Emergency Without Voltage (V) 12.00 Insulation class II

Dimmable No

Driver Remote included

Driver type Non Dimmable

Physical

ColorBlackRotation (°)360OrientationAdjustableRecessed depth (mm)170Weight (kg)0.45Tilt (°)40

Note

Accessory to reach IP54 incorporated. Pre-installation frame included in No Trim versions.