


Light Shooter HP Adjustable No Trim

■ 03.6573.14 - Black

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	592
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	11W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	29
Beam angle C90-270 (°)	29



Beam Angle: 29°		
<u>h(m)</u>	<u>E(lx)</u>	<u>D(m)</u>
1	1912	0.51
2	478	1.03
3	212	1.54
4	119	2.05
5	76	2.56

Luminous flux lumineuse
592 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Black	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	170		
Weight (kg)	0.45		
Tilt (°)	40		

Note

Accessory to reach IP54 incorporated. Pre-installation frame included in No Trim versions.

