




■ 03.6566.14.DA - Black

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.











			• ••		
IV/	ıaın	cna	cific	コキョヘコ	ne
1 7	ıaııı	300		auvi	13
		-			

number of neads	
_amp category	LED
Power (W)	11W
CCT (K)	2700K
CRI	90
CRI	90


Net lumen (lm) Mountings

412

Ceiling recessed Environment Indoor dry location

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15



Luminous flux luminaire 412 lm (EXTREME CUT OFF)

Bea	Beam Angle:		
<u>h(m)</u>	E(lx)	D(m)	
1	3740	0.26	
2	935	0.53	
3	416	0.79	
4	234	1.05	
5	150	1.31	

## **Electrical**

Frequency (Hz)	50/60	Insulation class
Dimmable	Yes	
Dutiness	Daniela Salaka da d	

Remote included Driver type Dimmable 1-10V, Dimmable

DALI 1

Emergency Without

## Physical

Color	Black
Orientation	Fixed
Trim	yes
Recessed depth (mm)	160
Weight (kg)	0.45

## Note

Accessory to reach IP54 incorporated.