



03.6579.40 - White

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.



| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 529 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 11W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

| | |
|------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | Power LED |
| Light distribution | Asymmetric |
| Optical type | Wall Washer |
| | Down |
| Beam angle (°) | 26 |
| Beam angle C90-270 (°) | 46 |



Luminous flux lumineuse
529 lm (EXTREME CUT OFF)

| | | |
|-------------|--------------|-------------|
| Beam Angle: | 26° | |
| <u>h(m)</u> | <u>E(lx)</u> | <u>D(m)</u> |
| 1 | 848 | 0.49 |
| 2 | 212 | 0.98 |
| 3 | 94 | 1.47 |
| 4 | 53 | 1.96 |
| 5 | 34 | 2.45 |

| | | | |
|----------------|-----------------|------------------|----|
| Frequency (Hz) | 50/60 | Insulation class | II |
| Dimmable | No | | |
| Driver | Remote included | | |
| Driver type | Non Dimmable | | |
| Emergency | Without | | |

| | |
|---------------------|-------|
| Color | White |
| Orientation | Fixed |
| Recessed depth (mm) | 160 |
| Weight (kg) | 0.45 |

Accessory to reach IP54 incorporated. Pre-installation frame included in No Trim versions.

