


## Light Sniper Adjustable Round

03.4683.06A - Chrome

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




## Main specifications

Number of heads	1	Net lumen (lm)	125
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	9W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	98		

## Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	23
Beam angle C90-270 (°)	23



Beam Angle: 23°

h(m)	E(lx)	D(m)
1	723	0.40
2	181	0.80
3	80	1.20
4	45	1.60
5	29	2.00


Luminous flux luminaire  
125 lm (EXTREME CUT OFF)

## Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

## Physical

Color	Chrome
Orientation	Adjustable
Recessed depth (mm)	125
Weight (kg)	0.51
Rotation (°)	360



# Light Sniper Adjustable Round



Concrete instalation can.  
08.8250.00



Ceiling protector accessory.  
08.8243.00



Ceiling protector accessory. 50 Units  
08.8243.00.5U



Flush ceiling round frame accessory  
08.8239.00B



Ceiling protector accessory. Round  
08.8229.30A



Ceiling protector accessory. 10 Units  
08.8243.00.1U