


Light Sniper Adjustable Round Dali

■ 03.4682.GLADA - Gold

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 248 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 9W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 98 | | |

Optical

| | |
|-------------------------------|--------------|
| Lighting type | Direct |
| LED type | Phosphor LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 35 |
| Beam angle C90-270 (°) | 35 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 35° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 814 | 0.63 | |
| 2 | 203 | 1.27 | |
| 3 | 90 | 1.90 | |
| 4 | 51 | 2.53 | |
| 5 | 33 | 3.17 | |


Luminous flux luminaire
248 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | |
|----------------------------|------------|
| Color | Gold |
| Orientation | Adjustable |
| Recessed depth (mm) | 125 |
| Weight (kg) | 0.51 |
| Rotation (°) | 360 |



Light Sniper Adjustable Round Dali



Ceiling protector accessory. Round
08.8229.30A



Ceiling protector accessory. 10 Units
08.8243.00.1U



Concrete instalation can.
08.8250.00



Ceiling protector accessory.
08.8243.00



Ceiling protector accessory. 50 Units
08.8243.00.5U



Flush ceiling round frame accessory
08.8239.00B