



## Light Sniper Adjustable Round Dimmable

■ 03.4984.14ADA - Matt black

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	297
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	11W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	15



Beam Angle: 15°

h(m)	E(lx)	D(m)
1	3197	0.26
2	799	0.52
3	355	0.78
4	200	1.04
5	128	1.30

Luminous flux luminaire  
297 lm (EXTREME CUT OFF)

### Electrical

<b>Dimmable</b>	Yes
<b>Driver</b>	Remote
<b>Driver type</b>	Electronic dimmable push, Electronic dimmable 1-10V, Electronic dimmable DALI
<b>Emergency</b>	Without
<b>Insulation class</b>	II

### Physical

<b>Color</b>	Matt black
<b>Orientation</b>	Adjustable
<b>Recessed depth (mm)</b>	155
<b>Weight (kg)</b>	0.65
<b>Rotation (°)</b>	360

## Light Sniper Adjustable Round Dimmable



---

Flush ceiling round frame accessory  
08.8239.00B



---

Ceiling protector accessory.  
08.8243.00




---

Ceiling protector accessory. 50 Units  
08.8243.00.5U



---

Ceiling protector accessory. 10 Units  
08.8243.00.1U



---

Concrete instalation can.  
08.8250.00



---

Ceiling protector accessory. Round  
08.8229.30A



---

Elliptical light distribution lens  
08.8041.68



---

Honeycomb  
08.8412.14