


## Light Sniper Adjustable Round Dimmable

03.4984.GLADA - Gold

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	297
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	11W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	15



<b>Beam Angle:</b>	15°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	3197	0.26	
2	799	0.52	
3	355	0.78	
4	200	1.04	
5	128	1.30	


Luminous flux luminaire  
297 lm (EXTREME CUT OFF)

### Electrical

<b>Dimmable</b>	Yes
<b>Driver</b>	Remote included
<b>Driver type</b>	Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
<b>Emergency</b>	Without
<b>Insulation class</b>	II

### Physical

<b>Color</b>	Gold
<b>Orientation</b>	Adjustable
<b>Recessed depth (mm)</b>	155
<b>Weight (kg)</b>	0.65
<b>Rotation (°)</b>	360



# Light Sniper Adjustable Round Dimmable



---


Ceiling protector accessory. 10 Units  
08.8243.00.1U

---

Elliptical light distribution lens  
08.8041.68

---

Honeycomb  
08.8412.14



---

Concrete installation can.  
08.8250.00

---

Ceiling protector accessory. 50 Units  
08.8243.00.5U

---

Ceiling protector accessory.  
08.8243.00



---

Ceiling protector accessory. Round  
08.8229.30A

---

Flush ceiling round frame accessory  
08.8239.00B