


Light Sniper Adjustable Round Dimmable

■ 03.4985.06.DA - Chrome

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 277 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 11W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 15 |
| Beam angle C90-270 (°) | 15 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 15° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 2978 | 0.26 | |
| 2 | 744 | 0.52 | |
| 3 | 331 | 0.78 | |
| 4 | 186 | 1.04 | |
| 5 | 119 | 1.30 | |


Luminous flux luminaire
277 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|--|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable Push, Dimmable 1- 10V, Dimmable DALI 1 | | |

Physical

| | |
|----------------------------|------------|
| Color | Chrome |
| Orientation | Adjustable |
| Recessed depth (mm) | 155 |
| Weight (kg) | 0.65 |
| Rotation (°) | 360 |



Light Sniper Adjustable Round Dimmable



Ceiling protector accessory. 50 Units
08.8243.00.5U




Ceiling protector accessory.
08.8243.00



Honeycomb
08.8412.14



Elliptical light distribution lens
08.8041.68



Concrete installation can.
08.8250.00



Ceiling protector accessory. 10 Units
08.8243.00.1U



Ceiling protector accessory. Round
08.8229.30A



Flush ceiling round frame accessory
08.8239.00B