

## Light Sniper Adjustable Square Dali

03.4686.06ADA - Chrome

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	281
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	9W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	98		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	36
<b>Beam angle C90-270 (°)</b>	35



<b>Beam Angle:</b>	36°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	897	0.65	
2	224	1.29	
3	100	1.94	
4	56	2.58	
5	36	3.23	



Luminous flux luminaire  
281 lm (EXTREME CUT OFF)

### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	Chrome
<b>Orientation</b>	Adjustable
<b>Recessed depth (mm)</b>	125
<b>Weight (kg)</b>	0.51
<b>Rotation (°)</b>	360



## Light Sniper Adjustable Square Dali




---

Flush ceiling square frame accessory  
08.8240.00B



---

Ceiling protector accessory. Square  
08.8222.30A



---

Concrete instalation can.  
08.8250.00



---

Ceiling protector accessory. 10 Units  
08.8243.00.1U



---

Ceiling protector accessory. 50 Units  
08.8243.00.5U



---

Ceiling protector accessory.  
08.8243.00