


Light Sniper Adjustable Square Dimmable

03.4987.GL.DA - Gold

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	338
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	11W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	14



Beam Angle:	13°	
h(m)	E(lx)	D(m)
1	3935	0.23
2	984	0.47
3	437	0.70
4	246	0.94
5	157	1.17


Luminous flux luminaire
338 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable push, Electronic dimmable 1-10V, Electronic dimmable DALI		

Physical

Color	Gold
Orientation	Adjustable
Recessed depth (mm)	155
Weight (kg)	0.65
Rotation (°)	360



Light Sniper Adjustable Square Dimmable



Flush ceiling square frame accessory
08.8240.00B



Ceiling protector accessory.
08.8243.00



Ceiling protector accessory. 50 Units
08.8243.00.5U



Ceiling protector accessory. 10 Units
08.8243.00.1U



Concrete installation can.
08.8250.00



Ceiling protector accessory. Square
08.8222.30A



Elliptical light distribution lens
08.8041.68



Honeycomb
08.8412.14