

Light Sniper Adjustable Square Dimmable

03.4999.06.DA - Chrome

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	503
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	11W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	25
Beam angle C90-270 (°)	27



Beam Angle:	25°		
h(m)	E(lx)	D(m)	
1	1846	0.45	
2	462	0.89	
3	205	1.34	
4	115	1.79	
5	74	2.24	



Luminous flux luminaire
503 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable Push, Dimmable 1- 10V, Dimmable DALI 1		

Physical

Color	Chrome
Orientation	Adjustable
Recessed depth (mm)	155
Weight (kg)	0.65
Rotation (°)	360



Light Sniper Adjustable Square Dimmable



Concrete instalation can.
08.8250.00



Ceiling protector accessory. 10 Units
08.8243.00.1U



Ceiling protector accessory. 50 Units
08.8243.00.5U




Ceiling protector accessory.
08.8243.00



Ceiling protector accessory. Square
08.8222.30A



Honeycomb
08.8412.14



Flush ceiling square frame accessory
08.8240.00B



Elliptical light distribution lens
08.8041.68