


03.4632.06A - Chrome


High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.



Number of heads	1
Lamp category	LED
Power (W)	9W
CCT (K)	3000K
CRI	98

Net lumen (lm)	138
Mountings	Ceiling recessed
Environment	Indoor dry location

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	23
Beam angle C90-270 (°)	23



Beam Angle: 23°

h(m)	E(lx)	D(m)
1	734	0.41
2	183	0.82
3	82	1.23
4	46	1.64
5	29	2.05

Luminous flux luminaire
138 lm (EXTREME CUT OFF)

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Remote included
Driver type	Non Dimmable

Emergency	Without
Insulation class	II

Color	Chrome
Orientation	Fixed
Recessed depth (mm)	115
Weight (kg)	0.51

Light Sniper Fixed Round



Ceiling protector accessory. 50 Units
08.8243.00.5U



Flush ceiling round frame accessory
08.8239.00B



Ceiling protector accessory. Round
08.8229.30A



Ceiling protector accessory. 10 Units
08.8243.00.1U



Concrete installation can.
08.8250.00



Ceiling protector accessory.
08.8243.00