



03.4981.GL - Gold


High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.



Number of heads	1
Lamp category	LED
Power (W)	11W
CCT (K)	2700K
CRI	90

Net lumen (lm)	351
Mountings	Ceiling recessed
Environment	Indoor dry location

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	15
Beam angle C90-270 (°)	15



Beam Angle: 15°

h(m)	E(lx)	D(m)
1	3180	0.27
2	795	0.53
3	353	0.80
4	199	1.07
5	127	1.33

Luminous flux lumineire
351 lm (EXTREME CUT OFF)

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Remote included
Driver type	Non Dimmable

Emergency	Without
Insulation class	II

Color	Gold
Orientation	Fixed
Recessed depth (mm)	165
Weight (kg)	0.49

Light Sniper Fixed Round



Ceiling protector accessory. 50 Units
08.8243.00.5U



Flush ceiling round frame accessory
08.8239.00B



Elliptical light distribution lens
08.8041.68



Ceiling protector accessory. 10 Units
08.8243.00.1U



Concrete instalation can.
08.8250.00



Ceiling protector accessory.
08.8243.00



Honeycomb
08.8412.14



Ceiling protector accessory. Round
08.8229.30A