



03.4992.GLA - Gold

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.



|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 599                 |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 11W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 28        |
| Beam angle C90-270 (°) | 28        |



Luminous flux lumineire  
599 lm (EXTREME CUT OFF)

|             |              |             |
|-------------|--------------|-------------|
| Beam Angle: | 28°          |             |
| <u>h(m)</u> | <u>E(lx)</u> | <u>D(m)</u> |
| 1           | 2036         | 0.51        |
| 2           | 509          | 1.01        |
| 3           | 226          | 1.52        |
| 4           | 127          | 2.02        |
| 5           | 81           | 2.53        |

|                |                 |                                       |               |
|----------------|-----------------|---------------------------------------|---------------|
| Frequency (Hz) | 50/60           | <b>Emergency<br/>Insulation class</b> | Without<br>II |
| Voltage (V)    | 220.00          |                                       |               |
| Dimmable       | No              |                                       |               |
| Driver         | Remote included |                                       |               |
| Driver type    | Non Dimmable    |                                       |               |

|                     |       |
|---------------------|-------|
| Color               | Gold  |
| Orientation         | Fixed |
| Recessed depth (mm) | 165   |
| Weight (kg)         | 0.49  |

Light Sniper Fixed Round



Ceiling protector accessory. 50 Units  
08.8243.00.5U



Flush ceiling round frame accessory  
08.8239.00B



Elliptical light distribution lens  
08.8041.68



Ceiling protector accessory. 10 Units  
08.8243.00.1U



Concrete instalation can.  
08.8250.00



Ceiling protector accessory.  
08.8243.00



Honeycomb  
08.8412.14



Ceiling protector accessory. Round  
08.8229.30A