

03.4993.GL - Gold


High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.

## Main specifications

Number of heads	1	Net lumen (lm)	558
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	11W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

## Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	28
Beam angle C90-270 (°)	28



Beam Angle: 28°

h(m)	E(lx)	D(m)
1	1897	0.51
2	474	1.01
3	211	1.52
4	119	2.02
5	76	2.53

Luminous flux lumineuse  
558 lm (EXTREME CUT OFF)

## Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

## Physical

Color	Gold
Orientation	Fixed
Recessed depth (mm)	165
Weight (kg)	0.49

Light Sniper Fixed Round



Ceiling protector accessory. 50 Units  
08.8243.00.5U



Flush ceiling round frame accessory  
08.8239.00B



Elliptical light distribution lens  
08.8041.68



Ceiling protector accessory. 10 Units  
08.8243.00.1U



Concrete instalation can.  
08.8250.00



Ceiling protector accessory.  
08.8243.00



Honeycomb  
08.8412.14



Ceiling protector accessory. Round  
08.8229.30A