



LED

11W

15

15

2700K 90

03.4981.GL.DA - Gold

Main specifications Number of heads

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.





6	•

Lamp category
Power (W)
CCT (K)
CRI

Beam angle (°)

Beam angle C90-270 (°)

Optical Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Spot

90°	1
	1
60°	6
	X
30° / 3180 cd / 30	0

Net lumen (lm)

Mountings

Environment

Lumino	ous flux luminaire
351 lm	(EXTREME CUT OFF)

1000	Bean	n Angle:	15°
90°	h(m)	E( <b>l</b> x)	D(m)
600	1	3180	0.27
//////X1	2	795	0.53
+++	3	353	0.80
	4	199	1.07
3180 cd 30°	5	127	1.33
3180 cd 30°	<u>4</u> 5		

Without

Ceiling recessed

Indoor dry location







## **Electrical**

Driver type

Frequency (Hz) 50/60 Voltage (V) Dimmable 220.00 Yes Driver Remote included

Dimmable Push, Dimmable 1-10V, Dimmable DALI 1

Emergency	Withou
Insulation class	II

## **Physical**

Color	Gold
Orientation	Fixed
Recessed depth (mm)	165
Weight (kg)	0.49

## Light Sniper Fixed Round Dimmable







Flush ceilling round frame accessory 08.8239.00B

Honeycomb 08.8412.14 Ceiling protector accessory. Round 08.8229.30A







Elliptical light distribution lens 08.8041.68

Ceiling protector accessory. 08.8243.00

Ceiling protector accessory. 50 Units 08.8243.00.5U





Ceiling protector accessory. 10 Units 08.8243.00.1U

Concrete instalation can. 08.8250.00