



03.4992.06ADA - Chrome

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.



Number of heads	1	Net lumen (lm)	599
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	11W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	28



Luminous flux lumineire
599 lm (EXTREME CUT OFF)

Beam Angle:	28°	
<u>h(m)</u>	<u>E(lx)</u>	<u>D(m)</u>
1	2036	0.51
2	509	1.01
3	226	1.52
4	127	2.02
5	81	2.53

Dimmable	Yes
Driver	Remote included
Driver type	Dimmable Push, Dimmable 1- 10V, Dimmable DALI 1
Emergency	Without
Insulation class	II

Color	Chrome
Orientation	Fixed
Recessed depth (mm)	165
Weight (kg)	0.49

Light Sniper Fixed Round Dimmable



Flush ceiling round frame accessory
08.8239.00B



Honeycomb
08.8412.14



Ceiling protector accessory. Round
08.8229.30A



Elliptical light distribution lens
08.8041.68



Ceiling protector accessory.
08.8243.00



Ceiling protector accessory. 50 Units
08.8243.00.5U



Ceiling protector accessory. 10 Units
08.8243.00.1U



Concrete instalation can.
08.8250.00