




## Light Sniper Fixed Round Dimmable

■ 03.4993.06.DA - Chrome

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	558
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	11W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	28
<b>Beam angle C90-270 (°)</b>	28



Beam Angle: 28°		
h(m)	E(lx)	D(m)
1	1897	0.51
2	474	1.01
3	211	1.52
4	119	2.02
5	76	2.53

Luminous flux luminaire  
558 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable Push, Dimmable 1- 10V, Dimmable DALI 1		

### Physical

<b>Color</b>	Chrome
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	165
<b>Weight (kg)</b>	0.49

## Light Sniper Fixed Round Dimmable



---

Ceiling protector accessory. 50 Units  
08.8243.00.5U



---

Ceiling protector accessory.  
08.8243.00



---

Honeycomb  
08.8412.14



---

Elliptical light distribution lens  
08.8041.68



---

Concrete installation can.  
08.8250.00



---

Ceiling protector accessory. 10 Units  
08.8243.00.1U



---

Ceiling protector accessory. Round  
08.8229.30A



---

Flush ceiling round frame accessory  
08.8239.00B