


Light Sniper Fixed Square

■ 03.4982.06A - Chrome

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	360
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	11W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	14
Beam angle C90-270 (°)	15



Beam Angle:	14°		
h(m)	E(lx)	D(m)	
1	3560	0.25	
2	890	0.50	
3	396	0.75	
4	222	0.99	
5	142	1.24	




Luminous flux luminaire
360 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical

Color	Chrome
Orientation	Fixed
Recessed depth (mm)	165
Weight (kg)	0.49



Light Sniper Fixed Square




Ceiling protector accessory. 10 Units
08.8243.00.1U



Elliptical light distribution lens
08.8041.68



Honeycomb
08.8412.14



Concrete installation can.
08.8250.00




Ceiling protector accessory. 50 Units
08.8243.00.5U



Ceiling protector accessory.
08.8243.00



Ceiling protector accessory. Square
08.8222.30A



Flush ceiling square frame accessory
08.8240.00B