


Light Sniper Fixed Square

03.4995.GL - Gold

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	537
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	11W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	26
Beam angle C90-270 (°)	27



Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1887	0.47
2	472	0.93
3	210	1.40
4	118	1.87
5	75	2.34



Luminous flux luminaire
537 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical


Color	Gold
Orientation	Fixed
Recessed depth (mm)	165
Weight (kg)	0.49



Light Sniper Fixed Square



Ceiling protector accessory. 50 Units
08.8243.00.5U



Flush ceiling square frame accessory
08.8240.00B



Elliptical light distribution lens
08.8041.68



Ceiling protector accessory. 10 Units
08.8243.00.1U



Concrete installation can.
08.8250.00



Ceiling protector accessory.
08.8243.00



Honeycomb
08.8412.14



Ceiling protector accessory. Square
08.8222.30A