







Light Sniper Fixed Square Dimmable

03.4982.GLADA - Gold

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.

Main specifications


| Number of heads | 1 |
|-----------------|-------|
| Lamp category | LED |
| Power (W) | 11W |
| CCT (K) | 3000K |
| CRI | 90 |

Net lumen (lm) 360 Mountings

Ceiling recessed Environment Indoor dry location

Optical

| Lighting type | Direct |
|--------------------|-----------|
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 14 |
| | |



Luminous flux luminaire 360 lm (EXTREME CUT OFF)

| Bear | m Angle: | 14° |
|------|----------------|------|
| h(m) | E(l x) | D(m) |
| 1 | 3560 | 0.25 |
| 2 | 890 | 0.50 |
| 3 | 396 | 0.75 |
| 4 | 222 | 0.99 |
| 5 | 142 | 1.24 |

Electrical

| Dimmable | Yes |
|-------------|-----------------|
| Driver | Remote included |
| Driver type | Dimmable Push, |
| | Dimmable 1- |
| | 10V, Dimmable |
| | |

DALI 1

Emergency Insulation class Without

Physical

| Color | Gold |
|---------------------|-------|
| Orientation | Fixed |
| Recessed depth (mm) | 165 |
| Weight (kg) | 0.49 |

Light Sniper Fixed Square Dimmable







Honeycomb 08.8412.14

Ceiling protector accessory. Square 08.8222.30A

Elliptical light distribution lens 08.8041.68







Ceiling protector accessory. 08.8243.00

Flush ceilling square frame accessory 08.8240.00B

Ceiling protector accessory. 50 Units 08.8243.00.5U





Ceiling protector accessory. 10 Units 08.8243.00.1U

Concrete instalation can. 08.8250.00