

Light Sniper Wall-Washer Round

03.4988.06A - Chrome

High-performance recessed luminaire with LED light source. Remote 220-240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	346
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	11W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Indirect, Direct
LED type	Power LED
Light distribution	Asymmetric
Optical type	Wall Washer
	Down
Beam angle (°)	35
Beam angle C90-270 (°)	35



Beam Angle:	35°		
	h(m)	E(lx)	D(m)
1	652	0.63	
2	163	1.26	
3	72	1.90	
4	41	2.53	
5	26	3.16	



Luminous flux luminaire
346 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical

Color	Chrome
Orientation	Fixed
Recessed depth (mm)	145
Weight (kg)	0.49



Light Sniper Wall-Washer Round



Ceiling protector accessory.
08.8243.00



Honeycomb
08.8412.14



Flush ceiling round frame accessory
08.8239.00B



Ceiling protector accessory. 50 Units
08.8243.00.5U



Elliptical light distribution lens
08.8041.68



Ceiling protector accessory. Round
08.8229.30A



Concrete installation can.
08.8250.00



Ceiling protector accessory. 10 Units
08.8243.00.1U