

03.4300.30B - White


Recessed luminaire with LED light source. Power supply not included.

## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 734                 |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 9.2W  | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 18        |
| Beam angle C90-270 (°) | 18        |



Luminous flux luminaire  
734 lm

|             |              |             |
|-------------|--------------|-------------|
| Beam Angle: | 20°          |             |
| <u>h(m)</u> | <u>E(lx)</u> | <u>D(m)</u> |
| 1           | 2748         | 0.35        |
| 2           | 687          | 0.70        |
| 3           | 305          | 1.04        |
| 4           | 172          | 1.39        |
| 5           | 110          | 1.74        |

## Electrical

|                    |                                                                                                     |                         |     |
|--------------------|-----------------------------------------------------------------------------------------------------|-------------------------|-----|
| <b>Voltage (V)</b> | 18.40                                                                                               | <b>Insulation class</b> | III |
| <b>Dimmable</b>    | Yes                                                                                                 |                         |     |
| <b>Driver</b>      | Remote excluded                                                                                     |                         |     |
| <b>Driver type</b> | Non Dimmable, Dimmable DALI 2, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming |                         |     |
| <b>Emergency</b>   | Without                                                                                             |                         |     |

## Physical

|                     |       |
|---------------------|-------|
| Color               | White |
| Orientation         | Fixed |
| Recessed depth (mm) | 88    |
| Weight (kg)         | 0.15  |

## Light Soldier Fixed Ø 75



Continuous current power supply  
220/240V – 50/60Hz. Adjustable Current  
300mA-13W / 350mA-15W / 400mA-18W  
/ 450mA-20W / 500mA-22W / 550mA-  
24W / 600mA-27W / 650mA-29W /  
700mA-31W / 750mA-32W / 800mA-33W  
/ 850mA-35W / 900mA-38W / 950mA-  
40W / 1000/1050mA-42W  
60.9162

Non dimmable continuous current  
power supply of 220/240V – 50/60Hz  
with power current selected through  
adjustable with switch 200 mA – 8,5W /  
300 mA – 13W / 350 mA – 15W / 400 mA  
– 17,5W / 450 mA – 19,5W / 500 mA –  
22W  
60.9160

Continuous current power supply,  
dimmable Casambi 220/240V-50/60Hz,  
300mA-16W / 350mA-18,5W / 400mA-  
21,5W / 450mA-24W / 500mA-27W /  
600mA-32W / 650mA-35W / 700mA-36W  
/ 750/800/900/1000/1050mA – 38W  
60.9207



Continuous current power supply of  
10-20W, 110/240V – 50/60Hz with power  
current selected through adjustable  
250 mA – 10W / 350 mA – 15W / 400 mA  
– 17W / 450 mA – 19W / 500/550/600/700  
mA – 20W, Dali 1 switch.  
60.8847

Continuous current power supply, 1-  
10V, regulable Mains, leading & trailing  
edge 220/240V – 50/60Hz, 500mA – 10W  
60.9411

Continuous current power supply of  
13-20W, 110/240V – 50/60Hz with power  
current selected through adjustable  
300 mA – 15W / 350 mA – 18W /  
400/450/500/550/600/  
650/700/750/800/850/900 mA – 15W.  
switch. 0/1-10V or push dimming  
60.9188



---

Continuous current power supply of  
12-20W, 110/240V – 50/60Hz with power  
current selected through adjustable  
350mA – 17W / 400mA – 19W / 450 / 550  
/ 600 / 700mA – 20W regulable Dali 1 y  
Dali 2  
60.9222