


Light Soldier Fixed Ø75

■ 03.4302.14B - Black


Recessed luminaire with LED light source. Power supply not included.

**Main specifications**

Number of heads	1	Net lumen (lm)	683
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	9.2W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	56
Beam angle C90-270 (°)	56



Beam Angle: 57°


h(m)	E(lx)	D(m)
1	910	1.08
2	227	2.15
3	101	3.23
4	57	4.30
5	36	5.38

Luminous flux luminaire
683 lm**Electrical**

Voltage (V)	18.40	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1- 10V, Electronic dimmable DALI		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Recessed depth (mm)	88
Weight (kg)	0.15

Certification / Marking

Light Soldier Fixed Ø75



Continuous current power supply of 12-20W, 110*/240V – 50/60Hz with power current selected through adjustable. Regulable DALI 1 y DALI 2
60.9222



Continuous current power supply of 13-42W, 220/240V – 50/60Hz with power current selected through adjustable switch
60.9162



Continuous current power supply, Mains dimming , 220/240V – 50/60Hz, 10W – 500mA.
60.9411



Continuous current power supply of 13-20W, 110*/240V – 50/60Hz with power current selected through adjustable switch. Synchronisation cables not included.
60.9188



Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 35W – 650mA / 36W – 700 mA.
60.9207



Constant Current Power Supply for LED. Dimmable DALI. 10-20W
60.8847



with power current selected through
adjustable with switch 200mA – 8,5W /
250mA – 11W / 300mA – 13W / 350mA –
15W / 400mA – 17,5W / 450mA 19,5W /
500mA – 22W.
60.9160