


Light Soldier Fixed Ø75

■ 03.4312.14A - Black

Recessed luminaire with LED light source. Power supply not included.




Main specifications

| | | | |
|-----------------|-------|----------------|------------------|
| Number of heads | 1 | Net lumen (lm) | 668 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 9.2W | Environment | Indoor |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 26 |
| Beam angle C90-270 (°) | 26 |



Beam Angle: 27°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1798 | 0.48 |
| 2 | 450 | 0.95 |
| 3 | 200 | 1.43 |
| 4 | 112 | 1.90 |
| 5 | 72 | 2.38 |

Luminous flux luminaire
668 lm


Electrical

| | | | |
|-------------|--|------------------|-----|
| Voltage (V) | 18.40 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI | | |
| Emergency | Without | | |

Physical

| | |
|---------------------|-------|
| Color | Black |
| Orientation | Fixed |
| Recessed depth (mm) | 88 |
| Weight (kg) | 0.15 |

Certification / Marking



Light Soldier Fixed Ø75



Continuous current power supply of 12-20W, 110*/240V – 50/60Hz with power current selected through adjustable. Regulable DALI 1 y DALI 2
60.9222



Continuous current power supply of 13-42W, 220/240V – 50/60Hz with power current selected through adjustable switch
60.9162



Continuous current power supply, Mains dimming , 220/240V – 50/60Hz, 10W – 500mA.
60.9411



Continuous current power supply of 13-20W, 110*/240V – 50/60Hz with power current selected through adjustable switch. Synchronisation cables not included.
60.9188



Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 35W – 650mA / 36W – 700 mA.
60.9207



Constant Current Power Supply for LED. Dimmable DALI. 10-20W
60.8847



with power current selected through
adjustable with switch 200mA – 8,5W /
250mA – 11W / 300mA – 13W / 350mA –
15W / 400mA – 17,5W / 450mA 19,5W /
500mA – 22W.
60.9160