


## Light Soldier Fixed Ø75

■ 03.4313.14A - Black

Recessed luminaire with LED light source. Power supply not included.




## Main specifications

|                 |       |                |                  |
|-----------------|-------|----------------|------------------|
| Number of heads | 1     | Net lumen (lm) | 652              |
| Lamp category   | LED   | Mountings      | Ceiling recessed |
| Power (W)       | 9.2W  | Environment    | Indoor           |
| CCT (K)         | 2700K |                |                  |
| CRI             | 90    |                |                  |

## Optical

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | LED array  |
| Light distribution     | Symmetric  |
| Optical type           | Wide flood |
| Beam angle (°)         | 56         |
| Beam angle C90-270 (°) | 56         |



Beam Angle: 57°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 868   | 1.08 |
| 2    | 217   | 2.15 |
| 3    | 96    | 3.23 |
| 4    | 54    | 4.30 |
| 5    | 35    | 5.38 |

Luminous flux luminaire  
652 lm


## Electrical

|             |                                                                                            |                  |     |
|-------------|--------------------------------------------------------------------------------------------|------------------|-----|
| Voltage (V) | 18.40                                                                                      | Insulation class | III |
| Dimmable    | Yes                                                                                        |                  |     |
| Driver      | Remote                                                                                     |                  |     |
| Driver type | Electronic,<br>Electronic dimmable,<br>Electronic dimmable 1-10V, Electronic dimmable DALI |                  |     |
| Emergency   | Without                                                                                    |                  |     |

## Physical

|                     |       |
|---------------------|-------|
| Color               | Black |
| Orientation         | Fixed |
| Recessed depth (mm) | 88    |
| Weight (kg)         | 0.15  |

## Certification / Marking



## Light Soldier Fixed Ø75



---

Continuous current power supply of 12-20W, 110\*/240V – 50/60Hz with power current selected through adjustable. Regulable DALI 1 y DALI 2  
60.9222



---

Continuous current power supply of 13-42W, 220/240V – 50/60Hz with power current selected through adjustable switch  
60.9162



---

Continuous current power supply, Mains dimming , 220/240V – 50/60Hz, 10W – 500mA.  
60.9411



---

Continuous current power supply of 13-20W, 110\*/240V – 50/60Hz with power current selected through adjustable switch. Synchronisation cables not included.  
60.9188



---

Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 35W – 650mA / 36W – 700 mA.  
60.9207



---

Constant Current Power Supply for LED. Dimmable DALI. 10-20W  
60.8847



with power current selected through  
adjustable with switch 200mA – 8,5W /  
250mA – 11W / 300mA – 13W / 350mA –  
15W / 400mA – 17,5W / 450mA 19,5W /  
500mA – 22W.  
60.9160