


## Light Soldier Fixed Ø75

03.4313.30A - White

Recessed luminaire with LED light source. Power supply not included.




## Main specifications

Number of heads	1	Net lumen (lm)	652
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	9.2W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

## Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	56
Beam angle C90-270 (°)	56



Beam Angle: 57°

h(m)	E(lx)	D(m)
1	868	1.08
2	217	2.15
3	96	3.23
4	54	4.30
5	35	5.38

Luminous flux luminaire  
652 lm


## Electrical

Voltage (V)	18.40	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1- 10V, Electronic dimmable DALI		
Emergency	Without		

## Physical

Color	White
Orientation	Fixed
Recessed depth (mm)	88
Weight (kg)	0.15

## Certification / Marking



## Light Soldier Fixed Ø75



Continuous current power supply of 12-20W, 110\*/240V – 50/60Hz with power current selected through adjustable. Regulable DALI 1 y DALI 2  
60.9222



Continuous current power supply of 13-42W, 220/240V – 50/60Hz with power current selected through adjustable switch  
60.9162



Continuous current power supply, Mains dimming , 220/240V – 50/60Hz, 10W – 500mA.  
60.9411



Continuous current power supply of 13-20W, 110\*/240V – 50/60Hz with power current selected through adjustable switch. Synchronisation cables not included.  
60.9188



Continuous current power supply, dimmable Casambi, 220/240V – 50/60Hz, 35W – 650mA / 36W – 700 mA.  
60.9207



Constant Current Power Supply for LED. Dimmable DALI. 10-20W  
60.8847



with power current selected through  
adjustable with switch 200mA – 8,5W /  
250mA – 11W / 300mA – 13W / 350mA –  
15W / 400mA – 17,5W / 450mA 19,5W /  
500mA – 22W.  
60.9160