

## Light Stripe 1200 mm

■ 03.7006.14 - Black

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.




## Main specifications

Lamp category	LED	Net lumen (lm)	1665
Power (W)	30W	Mountings	Track
System power (W)	32.4	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

## Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	108
Beam angle C90-270 (°)	105
Efficiency (lm/W)	51.39



Beam Angle: 105°

h(m)	E(lx)	D(m)
1	596	2.76
2	149	5.52
3	66	8.28
4	37	11.04
5	24	13.81

Luminous flux luminaire  
1665 lm

## Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable		
Emergency	Without		

## Physical

Color	Black
Orientation	Fixed
Weight (kg)	1.36
Length (mm)	1206
Lifespan (L70 B10)	L80B50

## Note

For wireless lighting control, choose integrated Casambi versions. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

