



Light Stripe 1500 mm Casambi integrated

New

03.8004.14.CB - Black

Diffused LED light module to be installed in The Tracking Magnet System.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	957
Power (W)	30W	Mountings	Track
System power (W)	30	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	109
Beam angle C90-270 (°)	109
Efficiency (lm/W)	31.9



Beam Angle: 109°

h(m)	E(lx)	D(m)
1	341	2.80
2	85	5.59
3	38	8.39
4	21	11.18
5	14	13.98

Luminous flux luminaire
957 lm

Electrical

Voltage (V)	48	Emergency	Without
Current (mA)	640	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.52
Length (mm)	1500
Lifespan (L70 B10)	L80B50

Note

Opal end covers not included. They must be ordered separately (08.0125.00 includes two units). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

