

Light Stripe 1500 mm Dali Version

■ 03.8004.14.DA - Black

Diffused LED light module to be installed in The Tracking Magnet System.




Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	957
Power (W)	30W	Mountings	Track
System power (W)	30	Environment	Indoor dry location
CCT (K)	2700K		

Optical



Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	109
Beam angle C90-270 (°)	109
Efficiency (lm/W)	31.9



Beam Angle: 109°

h(m)	E(lx)	D(m)
1	341	2.80
2	85	5.59
3	38	8.39
4	21	11.18
5	14	13.98

Luminous flux luminaire
957 lm



Electrical

Voltage (V)	48	Emergency	Without
Current (mA)	640	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI 1		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.52
Length (mm)	1500
Lifespan (L70 B10)	L80B50

Note

Opal end covers not included. They must be ordered separately (08.0125.00 includes two units). Only compatible with DALI profile version. For wireless lighting control, choose integrated Casambi versions.

