

## Light Stripe 300 mm

■ 03.7001.14 - Black

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.




### Main specifications

Lamp category	LED	Net lumen (lm)	440
Power (W)	7.5W	Mountings	Track
System power (W)	7.9	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	108
Beam angle C90-270 (°)	105
Efficiency (lm/W)	55.7



Beam Angle: 105°

h(m)	E(lx)	D(m)
1	158	2.76
2	39	5.52
3	18	8.28
4	10	11.04
5	6	13.81

Luminous flux luminaire  
440 lm

### Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable		
Emergency	Without		

### Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.34
Length (mm)	306
Lifespan (L70 B10)	L80B50

### Note

For wireless lighting control, choose integrated Casambi versions. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

