

## Light Stripe 300 mm Casambi integrated

New

### 03.7000.14.CB - Black


Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

### Main specifications

Lamp category	LED	Net lumen (lm)	416
Power (W)	7.5W	Mountings	Track
System power (W)	7.9	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	108
Beam angle C90-270 (°)	105
Efficiency (lm/W)	52.66



Beam Angle: 108°

h(m) E(lx) D(m)

1 149 2.76

2 37 5.52

3 17 8.28

4 9 11.04

5 6 13.81

Luminous flux luminaire  
416 lm

### Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		
Emergency	Without		

### Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.34
Length (mm)	306
Lifespan (L70 B10)	L80B50

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

