

Light Stripe 300 mm Casambi integrated

New

03.7001.14.CB - Black


Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

Main specifications

Lamp category	LED	Net lumen (lm)	440
Power (W)	7.5W	Mountings	Track
System power (W)	7.9	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	108
Beam angle C90-270 (°)	105
Efficiency (lm/W)	55.7



Beam Angle: 108°

h(m) E(lx) D(m)

1 158 2.76

2 39 5.52

3 18 8.28

4 10 11.04

5 6 13.81

Luminous flux luminaire
440 lm

Electrical

Voltage (V)	24.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.34
Length (mm)	306
Lifespan (L70 B10)	L80B50

Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

