



## Light Stripe 600 mm Casambi integrated

New

## ■ 03.8006.14.CB - Black

Diffused LED light module to be installed in The Tracking Magnet System.




## Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	405
Power (W)	12W	Mountings	Track
System power (W)	12	Environment	Indoor dry location
CCT (K)	3000K		

## Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	109
Beam angle C90-270 (°)	109
Efficiency (lm/W)	33.75



Beam Angle: 109°

h(m) E(lx) D(m)

1 144 2.80

2 36 5.59

3 16 8.39

4 9 11.18

5 6 13.98

Luminous flux luminaire  
405 lm

## Electrical

Voltage (V)	48	Emergency	Without
Current (mA)	250	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable Casambi		

## Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.21
Length (mm)	600
Lifespan (L70 B10)	L80B50

## Note

Opal end covers not included. They must be ordered separately (08.0125.00 includes two units). The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

