


## Light Stripe 600 mm On Board Dimmer

■ 03.8006.14 - Black

Diffused LED light module to be installed in The Tracking Magnet System.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	405
<b>Lamp category</b>	LED	<b>Mountings</b>	Track
<b>Power (W)</b>	12W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	109
<b>Beam angle C90-270 (°)</b>	109



Beam Angle: 109°

h(m)	E(lx)	D(m)
1	144	2.80
2	36	5.59
3	16	8.39
4	9	11.18
5	6	13.98

Luminous flux luminaire  
405 lm

### Electrical

<b>Voltage (V)</b>	48.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic 12V, Dimmer on board		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.21
<b>Length (mm)</b>	600

### Note

Opal end covers not included. They must be ordered separately (08.0125.00).

