

## Light Stripe 900 mm Casambi integrated

New

### 03.7005.14.CB - Black


Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.

### Main specifications

<b>Lamp category</b>	LED	<b>Net lumen (lm)</b>	1320
<b>Power (W)</b>	22.5W	<b>Mountings</b>	Track
<b>System power (W)</b>	22.5	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	108
<b>Beam angle C90-270 (°)</b>	105
<b>Efficiency (lm/W)</b>	58.67



Beam Angle: 108°

h(m)	E(lx)	D(m)
1	473	2.76
2	118	5.52
3	53	8.28
4	30	11.04
5	19	13.81

Luminous flux luminaire  
1320 lm

### Electrical

<b>Voltage (V)</b>	24.00	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable Casambi		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	1.02
<b>Length (mm)</b>	906
<b>Lifespan (L70 B10)</b>	L80B50

### Note

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

