

Light Stripe Dali Version 1200 mm

■ 03.7007.14.DA - Black

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.



Main specifications

| | | | |
|-----------------------|-------|--------------------|---------------------|
| Lamp category | LED | Mountings | Track |
| Power (W) | 30W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |
| Net lumen (lm) | 1760 | | |

Optical

| | | | |
|---------------------------|----------------|-------------------------------|-----|
| Lighting type | Direct | Beam angle C90-270 (°) | 105 |
| LED type | Top LED | | |
| Light distribution | Symmetric | | |
| Optical type | Diffused light | | |
| Beam angle (°) | 108 | | |

Electrical

| | | | |
|--------------------|-----------------|-------------------------|-----|
| Voltage (V) | 24.00 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |
| Emergency | Without | | |

Physical

| | |
|--------------------|-------|
| Color | Black |
| Orientation | Fixed |
| Weight (kg) | 1.36 |
| Length (mm) | 1206 |

Note

For wireless lighting control, choose integrated Casambi versions. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

