

Light Stripe Dali Version 600 mm

■ 03.7003.14ADA - Black

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.




Main specifications

Lamp category	LED	Net lumen (lm)	880
Power (W)	15W	Mountings	Track
System power (W)	16.1	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	108
Beam angle C90-270 (°)	105
Efficiency (lm/W)	54.66



Beam Angle: 108°

h(m)	E(lx)	D(m)
1	315	2.76
2	79	5.52
3	35	8.28
4	19	11.04
5	12	13.81

Luminous flux luminaire
880 lm



Electrical

Voltage (V)	24	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI		
	2		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	0.68
Length (mm)	606
Lifespan (L70 B10)	L80B50

Note

For wireless lighting control, choose integrated Casambi versions. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

